



## GENERAL INFORMATION

MX-841 is formulated as a universal elastomeric additive for use in 2-component coatings where flexibility is desired.



### 1. MIXING RATIO

- 10% by vol. to RTS mix



### 2. COMPATIBLE PRODUCTS

- Matrix 2K Urethane Primers
- Matrix Clearcoats
- Matrix Single-Stage

**\*Tech Note: DO NOT USE MX-841 IN THE FOLLOWING PRODUCTS: MP-EPOXIES, MATRIX DTM PRIMERS, MP-120 SERIES, MPB OR MSB BASECOAT PRODUCTS.**

\* Tech Note: Exceeding recommended mix ratio will result in slower flash and cure times.



### 3. PHYSICAL DATA

AS SUPPLIED REGULATORY DATA	10% by vol. to RTS mix	
	LBS./GAL.	g/L
Actual VOC	8.08	968.1975
Regulatory VOC (less water and exempt solvents)	5.0792	608.69
Density	7.780	--
	WT. %	VOL. %
Total Solids Content	34.67	30.13
Total Volatile Content	65.33	69.87
Water	0	0
Exempt Compound Content	0	0
Coating Category	Component	

## NOTES

If used as instructed, this product is designed to comply with the US National Volatile Organic Compound (VOC) Emission Standard for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BELIEVE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.