



# RSS-150

## READY TO SPRAY SEALER GREY

Technical Data Sheet  
Technical Hotline 800.735.0303

### PRODUCT#

RSS-150


### DESCRIPTION

READY TO SPRAY GREY SEALER



### DESCRIPTION

RSS-150 RTS Sealer Grey is a ready to spray single component sealer designed to provide a smooth uniform surface for basecoats. RSS-150 dries fast to a smooth uniform finish that allows quicker coverage and produces a higher quality final finish.



### MIXING

Must be mechanical agitated for 5-7 minutes.  
This product is Ready to Spray.



### APPLICATION

Apply 1-2 medium coats. Allow sealer to flash 30 minutes before topcoating or sanding at 77° F.



### DRYING AT 77° F.

FLASH BETWEEN COATS	10-15 MINUTES
NIB SAND	30 MINUTES
TO TOPCOAT	30 MINUTES

### TECHNICAL DATA

V.O.C. as Delivered:	Regulatory VOC in LBS./GAL.	Regulatory VOC in G./L.	Material VOC in LBS./GAL.	Material VOC in G./L.
RSS-150	4.6	554	3.2	385
V.O.C. (RTS):				
RSS-150	4.6	554	3.2	385

#### **Manufacturer's Exclusive Limited Warranty**

For Industrial use only by professional, trained personal using proper safety protective equipment. Not for sale to, or use by, the general public. Manufacturer warrants that its products are free from defect in material and workmanship at the time of sale. In the event that any product is proved by objective testing and analysis to have been defective at the time of sale, upon the return of the defective product, the manufacturer shall replace the product at no cost, excluding the shipping costs, as the exclusive remedy. This warranty does not cover damage caused by accident, misuse, improper application, improper combination of products or tampering. ALL IMPLIED WARRANTIES WHETHER IT BE OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. THIS WARRANTY EXCLUDES ALL INCIDENTAL AND CONSEQUENTIAL DAMAGES.

**NOTE: Refinish Solutions products are not recommended for use in temperatures below 60° F.**

**Use below these temperatures will effect dry times and performance.**

#### **FOR INDUSTRY USE ONLY**

**Read SDS Before Use**

Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions.

The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

**SEE SDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.**