

3.5 Single Stage Polyurethane MSU

MATRIX
SYSTEM
AUTOMOTIVE FINISHES
A Subsidiary of Quest Specialty Chemicals™

NEW Product Introduction

Technical Hotline 800.735.0303

Matrix System Automotive Finishes proudly
announces the release of:

3.5 Single Stage Polyurethane System



NOTE: Matrix System products are not recommended for use in temperatures below 60° F. Use below these temperatures will effect dry times and performance.

The contents of the package must be blended with other components before the product can be used. Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions.

The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.

Put it to the test!
www.matrixsystem.com

3.5 SINGLE STAGE

Features/Benefits:

- Exceptional gloss and color
- May be applied direct to metal
- Excellent exposure protection
- 25 Factory pack colors

3.5 Single Stage Polyurethane Systems

Polyurethane Systems

A high solids, high gloss, low VOC polyurethane coating intended for use as a high performance protective maintenance coating for automotive applications and surfaces exposed to humidity, chemicals and corrosive elements.

Common Uses:

- Vehicles, implements and trailers
- Chemical processing plants
- Buildings, structural steel and roof decks
- Industrial plants and mills
- Refineries, storage tanks and piping
- Marine vessels and offshore structures

Technical Information:

Mix Ratio: 4:1
VOC: 3.5 lbs/g
Pot Life: 4 hours @ 75 °F
Application: Conventional/Airless
Dry Time: 16-24 hours
Film Build: 2.5 mils dry; 4.8 wet

Put it to the test!
www.matrixsystem.com