

EZ-BLEND™

Edge Blender

- Ready-to-spray
- Used to dissolve edges of various coatings
- Invisible blend without causing edge lift
- Eliminates sanding and buffing dry edges
- Saves time and labor

Contact Your Local
Jobber For More
Information



ORDERING INFORMATION:

MX-840 EZ Blend Edge Blender Quart 12/case

“Put it to the Test!”

MATRIX
SYSTEM
AUTOMOTIVE FINISHES

A Subsidiary of Quest Specialty Chemical™

Description:

EZ Blend™ Edge Blender MX-840 is a ready-to-spray blending solvent used to dissolve the edges of various coatings. MX-840 is designed to give an invisible blend without causing edge lift. EZ Blend saves time and labor and eliminates sanding and buffing dry edges.

Technical Data:

Color:	Clear
Mix Ratio:	Ready-to-spray
V.O.C:	7.3 lbs/gal or 877 g/l
Weight:	7.32 lbs/gal
Flashpoint:	40°F TOC
% Solids:	0%
Shelf Life:	Unlimited

Application:

EZ Blend is used as a blending solvent for blending and spot repair. Add MX-840 to a clean spray gun cup. Then, using low pressure mist a light coat onto the edge of the repair to melt in the dry overspray. **REMEMBER:** Avoid over wetting the blend edges. Allow to dry properly.

Ordering Information:

MX-840 EZ Blend Edge Blender Qt. 12/case

Matrix System Automotive Finishes
850 Ladd Road, Building E
Walled Lake, MI 48390
Phone: 800.668.8135 • Fax: 248.668.8134
www.matrixsystem.com

Competition:

PPG®	DX840
Transtar®	6364
Sherwin Williams®	BS10
DuPont®	19301S
U-Pol®	2043
R-M®	UBR200
BASF®	UBR100

Features:

- Ready-to-spray
- Used to dissolve edges of various coatings
- Invisible blend without causing edge lift
- Eliminates sanding and buffing dry edges



MATRIX
SYSTEM
AUTOMOTIVE FINISHES
A Subsidiary of Quest Specialty Chemical™

MX-840

EZ BLEND™ EDGE BLENDER

Technical Data Sheet

Technical Hotline 800.735.0303

PRODUCT NUMBER

MX-840

DESCRIPTION

EZ BLEND™ EDGE BLENDER

DESCRIPTION

EZ Blend™ Edge Blender MX-840 is a ready-to-spray blending solvent used to dissolve the edges of single stage or clearcoat systems. MX-840 is designed to give an invisible blend without causing edge lift. EZ Blend™ saves time and labor and eliminates sanding and buffing dry edges.

COMPATIBLE SUBSTRATES

- OEM FINISHES

MIXING RATIO



Ready to Spray

APPLICATION



1. Application of MX-840 must be performed after either a Matrix System Single Stage or Clearcoat system to melt the wet edge of the blend.
2. Using the two gun method, adjust air pressure of the second gun containing MX-840 to 20-25 psi for conventional gravity or siphon feed and 5 psi at the cap for HVLP.
3. Apply 1-2 even wet coats to melt in blend area as necessary.

***Tech Tip:** MX-840 may be added to clearcoat residue in emptied spray gun cup as alternative method, **DO NOT** return this mixed product to MX-840 container.

***Tech Tip:** **DO NOT** over apply. Excessive application will result in runs or sags of product in blend area.

