

# MATERIAL SAFETY DATA SHEET

## QF-840

### SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: EZ Blend Edge Blender HMIS CODES: H 2 F 4 R 0 P X  
Product Code: QF-840

Distributed by:



Address: 850 Ladd Road, Building E  
Walled Lake, MI 48390

Emergency Phone: 800.424.9300 (CHEMTREC)  
Information Phone: 800.735.0303  
Web Site: [www.matrixsystem.com](http://www.matrixsystem.com)

Date Printed: August 26, 2009  
Prepared by: MSDS Coordinator

### SECTION II - COMPOSITION, INFORMATION ON INGREDIENTS

Name/Exposure Limits	CAS Number	Vapor Pressure	LEL	Percent by weight
ALIPHATIC PETROLEUM DISTILLATE ACGIH TLV-TWA = 300 ppm ACGIH TLV-STEL = NO INFO LD50(ORAL) = 5840 mg/kg LD50(DERMAL) = 2920 mg/kg LC50 = 10000 mg/m <sup>3</sup>	64742-89-8 EINECS 265-192-2		0.90	4.0000

## MATERIAL SAFETY DATA SHEET

### QF-840

Name/Exposure Limits	CAS Number	Vapor Pressure	LEL	Percent by weight
n-BUTYL ACETATE ACGIH TLV-TWA = 150 ppm ACGIH TLV-STEL = 200 ppm OSHA PEL-TWA = 150 ppm COMPANY = N.E.	123-86-4 EINECS 204-658-1		1.40	5.0000
ETHYL BENZENE ACGIH TLV-TWA = 100 ppm ACGIH TLV-STEL = 125 ppm OSHA PEL-TWA = 100 ppm OSHA PEL-STEL = 125 ppm Other = IARC (2B); CA PROP 65 (CANCER 6/11/2004) LD50(ORAL) = 3500 mg/kg (rat) LD50(DERMAL) = 20574 mg/kg (rabbit) LC50 = 17623 mg/m <sup>3</sup> (rat)	100-41-4 EINECS 202-849-4	19 mm Hg @ 68° F	1.20	4.9600
n-BUTANE ACGIH TLV-TWA = 800 ppm ACGIH TLV-STEL = NO INFO OSHA PEL-TWA = 800 ppm COMPANY = N.E. LD50(ORAL) = N.A. LD50(DERMAL) = N.A. LC50 = 658000 mg/m <sup>3</sup> (rat)	106-97-8 EINECS 203-448-7	879.10 mm Hg @ 68° F	1.80	6.0000
PROPANE ACGIH TLV-TWA = 1000 ppm ACGIH TLV-STEL = NO INFO LD50(ORAL) = N.A. LD50(DERMAL) = N.A. LC50 = NO INFO	74-98-6 EINECS 200-827-9	5585.2 mm Hg @ 68° F	2.20	17.0000

# MATERIAL SAFETY DATA SHEET

## QF-840

Name/Exposure Limits	CAS Number	Vapor Pressure	LEL	Percent by weight
XYLENE ACGIH TLV-TWA = 100 ppm ACGIH TLV-STEL = 150 ppm OSHA PEL-TWA = 100 ppm OSHA PEL-STEL = 150 ppm COMPANY = N.E. LD50(ORAL) = 4300 mg/kg (rat) LD50(DERMAL) = 1700 mg/kg (rabbit) LC50 = 18892 mg/m <sup>3</sup> (rat)	1330-20-7 EINECS 215-535-7	6.6 mm Hg @ 68° F	1.00	21.0000
GLYCOL ETHER PM ACETATE PROPYLENE GLYCOL METHYL ETHER ACETATE ACGIH TLV-TWA = N.E. ACGIH TLV-STEL = N.E. LD50(ORAL) = 8500 mg/kg (rat) LD50(DERMAL) = 5000 mg/kg (rat) LC50 = 5321 mg/m <sup>3</sup> (rat)	108-65-6 EINECS 203-603-9	3.7 mm Hg @ 68° F	1.30	26.0000

This product contains one or more reported carcinogens or suspected carcinogens which are noted by NTP, IARC or OSHA-Z in the other limits recommended column.

This substance is classified as a hazardous air pollutant.

---

### SECTION III - HAZARDS IDENTIFICATION

---

#### EMERGENCY OVERVIEW:

Causes eye irritation. Causes skin irritation. Vapors irritating to eyes and respiratory tract. Extremely flammable liquid and vapor. Vapors may cause flash fire or explosion. Extremely flammable aerosol. Contents under pressure.

#### EYE:

May cause severe eye irritation.

#### SKIN:

May cause skin irritation. Skin contact may aggravate an existing dermatitis.

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION III - HAZARDS IDENTIFICATION

---

#### **INHALATION:**

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation. Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death. Excessive inhalation of vapors can cause nasal and respiratory irritation. Liquid or vapor may be irritating to skin, eyes, throat or lungs. Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

#### **INGESTION:**

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis. Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

#### **CHRONIC EFFECTS:**

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Eye damage
- Liver damage
- Anemia

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Breathing air containing n-butyl acetate, which results from its use in aerosol applications, may cause delayed lung injury. In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION IV - FIRST AID MEASURES

---

#### EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists. Flush with large quantities of water for 15 minutes.

#### SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

#### INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

#### INGESTION:

Do not induce vomiting which can cause chemical pneumonitis and pulmonary edema. Contact a physician immediately.

---

### SECTION V - FIRE FIGHTING MEASURES

---

#### FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

**Flashpoint:** <25.0° F  
**Explosion Level:** Low (LEL) - 0.9  
High (UEL)- 13.1

#### EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

#### FIREFIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back. Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION VI - ACCIDENTAL RELEASE MEASURES

---

#### **CLEAN-UP AND CONTAINMENT:**

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire. Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

---

### SECTION VII - HANDLING AND STORAGE

---

#### **HANDLING:**

Wash hands thoroughly after handling. This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

*Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.*

#### **STORAGE:**

Store in a cool dry area with ventilation suitable for storing materials shown in section 2. Keep away from heat, sparks and flame. Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120° F.

---

### SECTION VIII - EXPOSURE CONTROLS, PERSONAL PROTECTION

---

#### **ENGINEERING CONTROLS:**

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

#### **RESPIRATORY PROTECTION:**

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

#### **SKIN PROTECTION:**

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

#### **EYE PROTECTION:**

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION VIII - EXPOSURE CONTROLS, PERSONAL PROTECTION

---

#### OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

#### HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

---

### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

---

Vapor Pressure:	5585.20 mm Hg @ 20° C
Vapor Density:	3.70
Boiling Range:	Lower - 1.0° F Higher - 302.0° F
Specific Gravity:	0.758
Formula Weight per Volume:	6.3081 lbs./gal.
VOC (Calculated, lbs./gal.):	6.308
VOC (Calculated, g./l.):	755.88
Percent Volatile by Weight:	100.0000
Percent Volatile by Volume:	100.0000
Evaporation Rate(n-butyl acetate = 1.0):	0.390
Viscosity:	N/A

---

### SECTION X - STABILITY AND REACTIVITY

---

#### CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame. Product may explode if heated. Keep cool, avoid exposure to heat.

#### INCOMPATIBILITIES:

Strong oxidizing agents.

#### DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

#### POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION X - STABILITY AND REACTIVITY

---

#### STABILITY:

The product is stable under normal storage conditions.

---

### SECTION XI - TOXICOLOGICAL INFORMATION

---

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

---

### SECTION XII - ECOLOGICAL INFORMATION

---

No specific ecological information is available for this product.

---

### SECTION XIII - DISPOSAL CONSIDERATIONS

---

#### WASTE DISPOSAL:

Place in closed containers. Dispose of the product in accordance with local, county, state and federal regulations.

---

### SECTION XIV - TRANSPORT INFORMATION

---

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II (Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL (Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL (Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

# MATERIAL SAFETY DATA SHEET

## QF-840

---

### SECTION XV - REGULATORY INFORMATION

---

#### SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

Chemical Name	CAS Number	Percent by weight
ETHYL BENZENE	100-41-4	4.9600
XYLENE	1330-20-7	21.1430
MIBK Methyl Isobutyl Ketone 4-methyl-2-pentanone	108-10-1	15.6620

#### FEDERAL REGULATIONS:

**TOXIC SUBSTANCES CONTROL ACT:** The chemical substances in this product are listed on the TSCA Section 8 inventory.

#### CALIFORNIA PROPOSITION 65

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

*Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.*

#### NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product:  
**NONE**

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %: **NONE**

#### INTERNATIONAL REGULATIONS:

**CANADA:** The chemical substances in this product are listed on the Canadian Domestic Substances List.

# **MATERIAL SAFETY DATA SHEET**

## **QF-840**

---

### **SECTION XVI - OTHER INFORMATION**

---

The information contained in this material safety data sheet is information from our suppliers and other sources. It is believed to be reliable. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

**Prepared on August 26, 2009**