

M A T E R I A L S A F E T Y D A T A S H E E T

FAST URETHANE REDUCER

Page: 1
3/11/2008

PRODUCT NAME: FAST URETHANE REDUCER
PRODUCT CODE: RSR-300-G

HMIS CODES: H F R P
2*3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURED BY : MATRIX SYSTEM Automotive Finishes, Inc.
ADDRESS : 850 Ladd Rd., Bldg. E
Walled Lake, MI 48390

EMERGENCY PHONE : (800)424-9300 DATE PRINTED : 3/11/2008
INFORMATION PHONE : (800)-735-0303 PREPARER NAME: MSDS Coordinator

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @ TEMP		PERCENT
ACETONE	67-64-1	185	68 F	54.11
ACGIH TLV STEL: 750 ppm				
ACGIH TLV TWA: 500 ppm				
OSHA VPEL TWA: 750 ppm				
OSHA VPEL STEL: 1000 ppm				
* TOLUENE	108-88-3	22	68 F	19.02
ACGIH TLV: 150 ppm STEL (SKIN)				
ACGIH TLV: 50 ppm TWA (SKIN)				
OSHA VPEL: 150 ppm STEL				
OSHA VPEL: 100 ppm TWA				
n-BUTYL ACETATE	123-86-4	8.4	68 F	9.91
ACGIH TLV TWA: 150 ppm				
ACGIH TLV STEL: 200 ppm				
OSHA VPEL TWA: 150 ppm				
OSHA VPEL STEL: 200 ppm				
light aliphatic naphtha	64742-89-8	60.0	68 F	0%-10%
400PPM TLV				
400PPM PEL				
n-HEPTANE	142-82-5	76	68 F	2.79
OSHA PEL: 400 ppm TWA				
OSHA PEL: 500 ppm STEL				
ACGIH TLV: 400 ppm TWA				
ACGIH TLV: 500 ppm STEL				
METHYLCYCLOHEXANE	108-87-2	82.74	100 F	.84
ACGIH TLV: 400 ppm TWA				
OSHA PEL: 400 ppm TWA				
XYLENES	1330-20-7	5.10	68 F	.38
ACGIH TWA 100 ppm				
ACGIH STEL 150 ppm				
OSHA TWA 100 ppm				
OSHA STEL 150 ppm				
CYCLOHEXANE	110-82-7	95.0	68 F	.28
300PPM TLV				
300PPM PEL				
ETHYL BENZENE	100-41-4	5.1	68 F	.07
OSHA PEL: 100 ppm TWA				
ACGIH TVL: 100 ppm TWA				

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
N/A

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 133 F - 281 F	SPECIFIC GRAVITY (H2O=1): .79
VAPOR DENSITY: N/A	EVAPORATION RATE: N/A
V.O.C. grams/liter: 802.97	V.O.C. lbs./gal.: 6.7
SOLUBILITY IN WATER: N/A	SOLIDS BY VOLUME: *****
APPEARANCE AND ODOR: N/A	

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: -4.0 F	METHOD USED: TAGCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0	UPPER: 15.0

EXTINGUISHING MEDIA: N/A

SPECIAL FIREFIGHTING PROCEDURES
N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS
N/A

===== SECTION V - REACTIVITY DATA =====

STABILITY: N/A
CONDITIONS TO AVOID
N/A

INCOMPATIBILITY (MATERIALS TO AVOID)
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
N/A

HAZARDOUS POLYMERIZATION: N/A

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
N/A

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
N/A

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
N/A

HEALTH HAZARDS (ACUTE AND CHRONIC)
N/A

CARCINOGENICITY: NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A
PROPOSITION 65 STATEMENT: WARNING! This product contains a chemical or chemicals known to the state of California to cause cancer and/or birth defects or other reproductive harm.

OSHA REGULATED: Yes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
N/A

EMERGENCY AND FIRST AID PROCEDURES
N/A

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
N/A

WASTE DISPOSAL METHOD
N/A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
N/A

OTHER PRECAUTIONS
N/A

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION
N/A

VENTILATION
N/A

PROTECTIVE GLOVES
N/A

EYE PROTECTION
N/A

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
N/A

WORK/HYGIENIC PRACTICES
N/A

===== SECTION IX - DISCLAIMER =====

N/A