

M A T E R I A L   S A F E T Y   D A T A   S H E E T

FX-10

Page 1 of 4

PRODUCT NAME: YELLOW  
PRODUCT CODE: FX-10

HMIS CODES: H F R P  
2 3 0 G

===== SECTION I - MANUFACTURER IDENTIFICATION =====

Manufacturer's Name: MATRIX SYSTEM Automotive Finishes, Inc.  
Address: 850 Ladd Road, Bldg. E  
Walled Lake, MI 48390



Prepared on: March 10, 2003

Emergency Telephone: (800) 424-9300 [CHEMTREC]  
Information Telephone: (800) 735-0303  
D.O.T. Hazard Classification: Paint  
Flammable Liquid  
UN 1263

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
* METHYL ETHYL KETONE OSHA VPEL: 200 ppm TWA OSHA VPEL: 300 ppm STEL ACGIH TLV: 200 ppm TWA ACGIH TLV: 300 ppm STEL	78-93-3	78	68 F	41%
1-METHOXY-2-PROPANOL ACGIH TLV: 100 ppm TWA ACGIH TLV: 150 ppm STEL	107-98-2	11.8	77 F	40-45%
SOLVENT YELLOW 72	4645-07-2	N/E	N/E	15-20%

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.



M A T E R I A L   S A F E T Y   D A T A   S H E E T

FX-10

Page 3 of 4

===== SECTION VI - HEALTH HAZARD DATA =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

May cause nose and throat irritation. Individuals with breathing problems must not be exposed to this product. If affected by inhalation, remove to fresh air. If breathing difficulty persists, consult a physician.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

May cause irritation of the eyes. Repeated and prolonged skin contact may cause skin irritation. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes; call a physician. In case of skin contact, wash with soap and water. If irritation occurs, contact a physician.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

Gastrointestinal distress. In the unlikely event of ingestion, call a physician immediately and have the names of all ingredients available.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE - Vapor may cause skin, eye, and/or respiratory irritation.  
CHRONIC - NONE KNOWN.

**CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No**

To the best of our knowledge this material contains no known carcinogens

**OSHA REGULATED:** Yes

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

Preexisting eye, skin, and respiratory conditions.

**EMERGENCY AND FIRST AID PROCEDURES**

Inhalation- remove from contaminated atmosphere. In case of massive exposure, get medical attention. Eyes- promptly flush with water for 15 minutes. Get medical attention.

M A T E R I A L   S A F E T Y   D A T A   S H E E T

FX-10

Page 4 of 4

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition (sparks, flames, and hot surfaces). Place in leak-proof drums

**WASTE DISPOSAL METHOD**

Dispose in accordance with state ,federal and local regulations. Do not incinerate closed containers.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Store away from high tempratures and open flames.

**OTHER PRECAUTIONS**

Do not take internally, avoid prolonged contact with skin.

===== SECTION VIII - CONTROL MEASURES =====

**RESPIRATORY PROTECTION**

Approved combination dust and vapor respirator.

**VENTILATION**

Provide general dillution or local ehxaust ventilation.

**PROTECTIVE GLOVES**

Solvent resistant.

**EYE PROTECTION**

Safety glasses.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

Safety eyewash station.

**WORK/HYGIENIC PRACTICES**

Follow general industrial hygiene. Ingredients in this product are listed in the TSCA inventory.

===== SECTION IX - DISCLAIMER =====

The information contained in this material safety data sheet is information from our suppliers and other sources. It is believed to be reliable. This data is not to be taken as a warranty or representation for which this company assumes legal responsibility.