



### GENERAL INFORMATION

MX-084 is formulated to reduce the cure, dust, tack and tape times of most Matrix Edge™ 2K Urethane Clearcoat products without sacrificing pot life. MX-084 can increase shop productivity and profitability when used properly.



### 1. MIXING RATIO

- Mix up to 1/2 oz. of MX-084 to 1 quart of Ready-to-Spray material.



### 2. COMPATIBLE PRODUCTS

- Matrix Edge Clearcoats
- Matrix Edge Single-Stage

\*Tech Note: Refer to individual product TDS

**\*Tech Note: CAN NOT BE USED IN MATRIX EDGE PRIMERS/SEALERS**



### 3. PHYSICAL DATA

AS SUPPLIED REGULATORY DATA	1/2:1	
	LBS./GAL.	g/L
Actual VOC	7.95	952
Regulatory VOC (less water and exempt solvents)	7.95	952
Density	8.09	--
	WT.%	VOL.%
Total Solids Content	1.77	1.63
Total Volatile Content	98.23	98.37
Water	0	0
Exempt Compound Content	0	0
Coating Category	Additive	

### NOTES

**If used as instructed, this product is designed to comply with the US National Volatile Organic Compound (VOC) Emission Standard for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use.** The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.