



RSP-120

2.1 VOC LACQUER PRIMER

Technical Data Sheet
Technical Hotline 800.735.0303

PRODUCT#

RSP-120

DESCRIPTION

2.1 VOC LACQUER PRIMER GREY

ACTIVATOR

N/A

DOES NOT REQUIRE AN ACTIVATOR

REDUCER

MR-100LV

LOW VOC REDUCER



DESCRIPTION

RSP-120 2.1 VOC Lacquer Primer is a high quality one component primer surfacer that is fast drying, easy sanding and is 2.1lbs/gal VOC compliant. RSP-120 provides great value for many applications.



MIXING

RSP-120
1 Part

TO

LOW VOC REDUCER
1 Part



APPLICATION

Apply 1-3 wet coats, allowing a 5-10 minute flash between coats at 77°F.

Important Note: Galvanized steel, bare metal and aluminum are required to be properly cleaned, sanded and treated prior to applying any primer surfacer. To obtain maximum performance always treat bare metal with a quality metal conditioning system.



DRYING AT 77° F.

TO FLASH

5-10 MINUTES

TO SAND

30 MINUTES

TO TOPCOAT

30 MINUTES

TECHNICAL DATA

V.O.C. as Delivered:	Regulatory VOC in LBS./GAL.	Regulatory VOC in G./L.	Material VOC in LBS./GAL.	Material VOC in G./L.
RSP-120	2.1	247	0.6	71
ZERO VOC REDUCER	0.0	0	0.0	0
V.O.C. (RTS):				
RSP-120/ ZERO VOC REDUCER	2.1	247	0.3	36

Manufacturer's Exclusive Limited Warranty

For Industrial use only by professional, trained personal using proper safety protective equipment. Not for sale to, or use by, the general public. Manufacturer warrants that its products are free from defect in material and workmanship at the time of sale. In the event that any product is proved by objective testing and analysis to have been defective at the time of sale, upon the return of the defective product, the manufacturer shall replace the product at no cost, excluding the shipping costs, as the exclusive remedy. This warranty does not cover damage caused by accident, misuse, improper application, improper combination of products or tampering. ALL IMPLIED WARRANTIES WHETHER IT BE OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. THIS WARRANTY EXCLUDES ALL INCIDENTAL AND CONSEQUENTIAL DAMAGES.

NOTE: Refinish Solutions products are not recommended for use in temperatures below 60° F.

Use below these temperatures will effect dry times and performance.

FOR INDUSTRY USE ONLY

Read SDS Before Use

Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions.

The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

SEE SDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.