



GENERAL INFORMATION

MX-081 is designed to reduce the cure rate of urethane paints, primers, and clearcoats in cold weather conditions. MX-081, when used properly, will dramatically shorten sanding, buffing and delivery times.



1. MIXING RATIO

- Mix up to 1/2 oz. of MX-081 to 1 quart of Ready-to-Spray material.



2. COMPATIBLE PRODUCTS

- Matrix Edge™ 2K Primers
 - Matrix Edge Clearcoats
 - Matrix Edge Single-Stage
- *Tech Note: Refer to individual product TDS*



3. PHYSICAL DATA

AS SUPPLIED REGULATORY DATA	1/2:1	
	LBS./GAL.	g/L
Actual VOC	7.24	868
Regulatory VOC (less water and exempt solvents)	7.24	868
Density	7.37	--
	WT.%	VOL.%
Total Solids Content	1.71	1.44
Total Volatile Content	98.29	98.56
Water	0	0
Exempt Compound Content	0	0
Coating Category	Additive	

NOTES

If used as instructed, this product is designed to comply with the US National Volatile Organic Compound (VOC) Emission Standard for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.